

WHE00109

EN



TECHNICAL DETAILS

STANDARD
EN 12492
CE UK CA

TEMPERATURE OF USE
-20°C / +35°C

WEIGHT
420 g

SIZE
Universal-adjustable from 51 to 62 cm

MATERIAL
EXTERNAL SHELL:
HD Polypropylene

INTERNAL SHELL:
Neopor® Cycled® by BASF | EPS obtained from chemical recycling of plastic waste.

○ WHE00109-201 WHITE	● WHE00109-223 RED FLUO
● WHE00109-210 BLACK	● WHE00109-224 LIME FLUO
● WHE00109-221 YELLOW FLUO	

CATEGORY
II

HEADBAND:
Soft PA Nylon

TECHNOLOGIES



HD EPS INTERNAL SHELL

Inner shell composed of high-density Neopor® Cycled® foam for all-around impact energy absorption and improved comfort.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



2DRY LINER

A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



EARMUFF ADAPTER ATTACHMENT POINTS

Helmet designed with attachment points for earmuff adapters. It allows KASK earmuffs to be integrated with helmet.



UP & DOWN SYSTEM

A size adjustment system comprised of three components for all-day comfort. A central dial allows easy size adjustments, and side wings ensure a snug fit against the back of the head. The patented Up & Down hinge with helmet stability technology adapts as the wearer moves to deliver a more secure and personalized fit.



VISOR ATTACHMENT POINTS

Helmet designed with attachment points for securing KASK eye protection accessories.



INTEGRATED LUMINISCENT LAMP CLIPS

Designed with 4 built-in, luminiscent nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.



VENTILATION CHANNELS

Helmet designed with 10 air intakes that maximize internal airflow through outflow channels providing exceptional helmet breathability.



HI-VIZ DETAILS

High visibility color shell, luminiscent lamp clips and high visibility reflective adhesives for added safety in low visibility conditions.



ANTI-INTRUSION MESH

Metal mesh vent covers that prevent debris from entering the ventilation channels while maintaining breathability.

PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J	Chinstrap release	K	>50 kg
Protection against front, lateral and rear impacts	K	5 kg from 0,5 m 25 J	Retention system effectiveness	K	
Protection against penetration of objects	K	3 kg from 1 m 30 J			

K EN 12492 standard requirements



Since 2019, every KASK helmet made has been tested with the KASK Rotational Impact WG11 Test. All KASK helmets have BrIC values <0.39.

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION